

Echo AIO-AT

Combination Acoustic and Digital Test Interface




The **Echo AIO-AT** is a combination acoustic and digital test interface built for production-line testing and QA/QC verification. Combining two 10W amplifier outputs, four mic/line analog inputs, and a 10-channel full duplex TDM bus in a single unit, the AIO-AT is an integrated, cost-effective, and reliable high-throughput audio test solution.

Each analog input can be individually configured as a line level input or as a measurement microphone input. Microphone inputs include an IEPE microphone conditioning amplifier with integrated constant current power supply (CCP).

The AIO-AT presents a standard USB audio sound card interface and is compatible with most audio test software including APx500 Flex, LabVIEW, SoundCheck, and ARTA.



Echo Test + Measurement
402 East Carrillo Street, Suite A
Santa Barbara, California 93101
USA
echotm.com
sales@echotm.com
805-880-5590



AIO-AT SPECIFICATIONS

Microphone / Line Inputs

Input bandwidth	72 kHz
Input impedance	1 M Ω
Input gain	1x, 10x, and 100x
Full-scale input voltage (1x gain)	8.75 Vpk
Maximum input voltage	15 Vpk (do not exceed)
Dynamic range (1x gain, A-weighted)	> 110 dB
THD+N (1x gain, A-weighted)	< -95 dB (20 Hz – 20 kHz)
Frequency response	± 0.5 dB (20 Hz – 20 kHz)
Constant current supply	4 mA, 21 V excitation voltage
TEDS	IEEE 1451.4 Class 1

Amplifier Outputs

Output power (THD+N < .1%)	10 W continuous at 1 kHz
Maximum output voltage	13.5 Vpk
Frequency response	± 0.5 dB (20 Hz – 20 kHz)

TDM

Channels	2, 4, 8, or 10
Clock source	Internal or external clock sync
Bits per frame	64, 128, or 256
Bits per sample	24 or 32
Frame sync width	1-128 bits
Frame sync position	Bit 0-255

Interface

Sample rate	48 kHz
USB	USB 2.0 audio class compliant
Supported operating systems	Windows 7 or later, macOS
Audio APIs	ASIO, WASAPI, CoreAudio
AC power	Universal power supply, 90 - 264 VAC at 50 or 60 Hz

Dimensions and Weight

Single unit	17.5" (44.4 cm) x 8.75" (22.2 cm) x 1.75" (4.4 cm), 7.2 lbs (3.3 kg)
Single unit boxed with cables	21" (53 cm) x 10" (25.4 cm) x 5" (12.7 cm), 8.75 lbs (4 kg)
Shipping carton (4 AIOs)	22" (55.8 cm) x 22" (55.8 cm) x 12.6" (32 cm), 42.5 lbs (19.3 kg)